

uTrust Smart Card Reader Dual

uTrust 470x F — Dual Interface Smart Card Reader



- **USER CONVENIENCE**
 Modern housing design optimized for easy and ergonomic operation even in space limited situations
- **CONVERGENCE**
 Featuring contact, contactless, Lascom, and NFC technologies for use with mixed credential populations
- **INTEROPERABLE**
 Supports major card ICs, standards, and technologies in just one device
- **FAST**
 Transaction time optimized with support of 848 kbps in ISO/IEC 14443 and 600 kbps in ISO/IEC 7816 for maximum end-user acceptance

The uTrust 470x F is the ideal combination of contact, contactless, and NFC technologies in just one single device.

Supporting ISO/IEC 7816 contact cards, 13.56 MHz contactless technology, and NFC, this PC-linked dual interface reader features end-user environments where virtually all kinds of credentials are being used, even in mixed populations.

With its all-in-one concept, the uTrust 470x F enables a smooth transition from well-established traditional technologies into emerging NFC applications, pushing new business.

It represents the perfect mix between modern, stylish design and the ergonomic use of any credential form factor, like ID-1 cards, tokens, or NFC-enabled smart phones.

The end user experiences convenience, transaction-time efficiency, security, flexibility, and full NFC capability for use applications such as network log-on, secure web-based transactions, governmental use applications like online tax-declarations, or even NFC-based customer loyalty programs.

PARAMETER	IDENTIV UTRUST 470X F
Host Interface	
Host Interface	USB 2.0 CCID (USB 1.1/3.0 compliant)
Communication Speed	12 Mbps (USB 2.0 full speed)
Smart Card Interface	
Supported Standards	ISO/IEC 7816 Part 1 to 4
Supported Tag ICs	All major ISO/IEC 7816 compliant Smart Card IC support
Smart Card Protocols	T=0, T=1
Smart Card Interface Speed	<ul style="list-style-type: none"> • Up to 600 kbps (depending on card) • TA1=97
Smart Card Clock Frequency	ISO/IEC 7816 compliant up to 5 MHz; Operates up to 12 MHz
Supported Smart Card Types	5V, 3V and 1.8V, ISO/IEC 7816 Class A/B/C
Power to Smart Card	60mA in Class A; 55mA in Class B; 35mA in Class C
Smart Card Detection	<ul style="list-style-type: none"> • Card present switch • Automatic power on/off • Short circuit protection
Card Size	ID-1
Contact Type	Sliding Contact Socket (8 pin)

uTrust Smart Card Reader Dual

uTrust 470x F — Dual Interface Smart Card Reader

PARAMETER	IDENTIV UTRUST 470X F
Contactless Interface	
Supported Standards	<ul style="list-style-type: none"> • ISO 14443 Part 1 to 4 • ISO 18092
Protocols	T=CL
Supported Card Chips	<ul style="list-style-type: none"> • Lascom Cards • MIFARE™ (Classic, Ultralight, Ultralight C, MIFARE PLUS, DESFire, DESFire EV1 2/4/8k), FeliCa™, Calypso, CD21, NFC Forum Tag types 1/2/3/4
Data Transfer Rate	<ul style="list-style-type: none"> • 106/212/424/848 kbps (depending on card IC)
Reading Distance	<ul style="list-style-type: none"> • Up to 10 mm/0.394 in for Lascom Cards • Up to 70 mm/2.756 in (depending on card chip type and card antenna size)
Antenna	Integrated
Driver and Software	
PC/SC Driver	PC/SC Specification Ver. 2.01.14 for: <ul style="list-style-type: none"> • Windows® 7/8 (32 and 64 Bit) • Windows® Server 2003/2008/2012 • MacOS 10.6.x, 10.7.x, 10.8.x, 10.9.x • Linux 2.6.x (32 and 64 Bit), 3.x
Software	<ul style="list-style-type: none"> • PC/SC API • CT-API (through wrapper on top of PC/SC) • M-Card API (through wrapper on top of PC/SC)
Operating Conditions	
Power Supply	Bus-powered USB
Power Consumption	<220 mA, excluding smart card; < 400 mA, with smart card; < 600 µA in Standby Mode
Dimensions	<ul style="list-style-type: none"> • 126 x 93 x 21 mm/4.961 x 3.661 x 0.827 in • uTrust 4701 F with stand foot kit: 128 x 93 x 90 mm/4.449 x 3.661 x 3.622 in
Weight	<ul style="list-style-type: none"> • 117 g ± 5% / 0.26 lb ± 5% • uTrust 4701 F with stand foot kit: 167 g ± 5% / 228 g ± 5%
Operating Temperature Range	-20° to +70° C / -4° to +158° F
Storage Temperature Range	-25° to +85° C / -13° to +185° F
Operating Humidity Range	Up to 95% RH non-condensing
Durability	Sliding Contact 100,000 card insertions
MTBF	~4M hours
Connector	1.5 m USB Cable with USB Type A Connector
Status Indicator	Dual color LED
Firmware	SmartOS™
Firmware In-Field Upgradeable	Yes
Certifications and Compliances	
Systems/Standards	ISO/IEC 7816, USB 2.0 Full Speed, CCID, Microsoft® WHQL
Regulatory/Environmental	CE, FCC, UL94, UL60950, VCCI, RFLJ, RoHS2, REACH, WEEE
Ordering Information	
Product Part Number	905504 - 5008; 905322



Identiv (NASDAQ: INVE) is a global security technology company that establishes trust in the connected world, including premises, information, and everyday items. CIOs, CSOs and product departments rely upon Identiv's trust solutions to reduce risk, achieve compliance, and protect brand identity. Identiv's trust solutions are implemented using standards-driven products and technology, such as digital certificates, strong authentication, mobility, and cloud services.

Identiv has offices worldwide. Addresses and phone numbers are listed at identiv.com/contact. For more information, visit identiv.com or email sales@identiv.com.

Technical data is subject to change without notice.

Copyright © 2015 Identiv, Inc. | All rights reserved. This document is Identiv public information.

Revision/Date of Release: 2015-1

identiv.com